



Friendliness

- Compact and light weight design for easy carrying and mounting
- Long runtime battery, for emergency and transfer, and saves electrical sockets
- Intuitive operation and easy to install IV sets

Safety

- Dynamic pressure display, prevents occlusion caused by small animal movement
- High sensitivity air bubble detection up to 50ul
- High waterproof up to IP34, supports cleaning with water

Connectivity

- WiFi connection available
- Dock support



BeneFusion VP1 Vet Volumetric Pump

mindray
healthcare within reach

BeneFusion VP1

Specifications	
Dimension	250 x 90 x 150mm
Weight	<1.45kg
Classification	CF, Class I
Infusion sets	Applicable to GB 8368-2005 disposals; diameters Φ 3.5-4.5mm, thickness 0.8-1.2mm
Screen	2.4" LCD monochrome screen
Basic Parameters	
Infusion mode	Rate mode, Drop rate mode
Flow rate range	0.1~600 ml/h
VTBI	0.1~9999 ml
Accumulated volume	0.1~9999 ml, increment is 0.1 ml
Preset time	00:00:01-99:59:59(h:m:s) adjustable
Increment	0.1 ml/h
Accuracy	$\leq \pm 5\%$
KVO rate	0.5 ml/h, unadjustable
Bolus rate	Manual Bolus: 0.2-600ml/h
Purge rate	600ml/h, unadjustable
Occlusion	Low 150 $\pm$ 113 mmHg (20kPa) Medium 525 $\pm$ 113 mmHg (70kPa) High 900 $\pm$ 180 mmHg (120 kPa)
Air bubble detection	Minimum 50ul; 5 levels selectable: 50ul, 100ul, 250ul, 500ul, 800ul; default is 100ul;
Functions	
Titration	Yes
Keypad lock	Yes
Pause	Yes
Anti-bolus	Yes
Self-test system	Yes
Alarm Volume	1-8 levels selectable
Language	11, Chinese, English, French, Russian, Turkish, Portuguese, Polish, Bulgarian, Czech, Romanian
Mounting Solution	
Dock	Supported
Handle	Included
Mounting type	Standard: Vertical Pole; Optional: Horizontal Pole
Alarm	
Visual and acoustic alarm	VTBI done, VTBI near done, KVO finish, air in line, door open, drop rate error, standby time expired, occlusion, system error, system abnormal, battery low, battery empty, reminder, AC power disconnection
Power Supply	
AC power	100-240V (50/60Hz)
Battery type	Lithium
Battery operation time	Standard: 4 hours@25ml/h; Optional: 8 hours@25ml/h
Charging time	< 6hours
Safety Requirement	
IP Grade	IP 34
Temperature	0~40°C for operating, -40~70°C for storage
Humidity	15~95% for operating, 10~95% for storage
Air pressure	57~106kPa for operating, 50~106kPa for storage
Connectivity	
Data interface	Supported, RS232
Wireless	WiFi (optional)
Nurse Call	Supported
DC input	Supported
Ambulance	Supported, meet EN-1789 requirement

Mindray Building, Keji 12th Road South,
High-tech Industrial Park, Nanshan, Shenzhen 518057, P.R. China
Tel: +86 755 8188 8998 Fax: +86 755 26582680
E-mail: intl-market@mindray.com www.mindray.com
Mindray is listed on the NYSE under the symbol "MR"

mindray | healthcare within reach are registered trademarks or trademarks owned by Shenzhen Mindray Bio-medical Electronics Co., LTD.
©2013 Shenzhen Mindray Bio-Medical Electronics Co., Ltd. All rights reserved. Specifications subject to changes without prior notice.
P/N:ENG-BeneFusion VP1 Vet volumetric pump-210285x2-20160104

mindray